

# NITTERHOUSE



MASONRY PRODUCTS, LLC

## WIND UPLIFT CONNECTION

DESIGNED FOR USE WITH  
OUR HIDDEN FASTENING  
KIT & PEDESTALS



## NITTERHOUSE PAVERS *WITH WIND UPLIFT CONNECTION*

**WIND RESISTANCE:** 160 mph

**COMPRESSION STRENGTH:** Avg 8500 psi

**WATER ABSORPTION:** Less than 5% (ASTM C140)



Nitterhouse's *NMP Paver Lockdown Pedestal* easily slides into the fixed connection on the pedestal. The connection is undetectably screwed into the corresponding reinforced top of the Nitterhouse pedestal to securely lock down the pavers ensuring a safe, secure, and level surface.

# NMP PAVER LOCKDOWN PEDESTAL

**Base Diameter:** 7 43/64" (195 mm)

**Slope Correction:** 0-4%

**Height Range:** 5/64"- 42 5/8" (2mm- 1083mm)

**Compressive Resistance:** 1,984lb minimum

**Material:** Recycled Polypropylene resistant to mold, alkali, & bitument

**Pedestal works with all  
Nitterhouse Architectural  
& Camina Paving Stones**



## NITTERHOUSE



MASONRY PRODUCTS, LLC