

# NITTERHOUSE



MASONRY PRODUCTS, LLC

## WIND UPLIFT CONNECTION

DESIGNED FOR USE WITH  
OUR HIDDEN FASTENING  
KIT & PEDESTALS



## NITTERHOUSE PAVERS WITH WIND UPLIFT CONNECTION

**WIND UPLIFT RESISTANCE:** 350 psf *(fully adhered systems-contact for details)*

**COMPRESSION STRENGTH:** Avg 8500 psi

**WATER ABSORPTION:** Less than 5% *(ASTM C140)*



**Nitterhouse Hydraulic Pressed Paver**

**Nitterhouse Paver Fastening Kit**

**Nitterhouse Pedestal**

Nitterhouse's Wind Uplift Connection pavers have an innovative slot in each corner allowing for a special washer and finishing screw to be inserted. After all pavers are placed, the Nitterhouse Tie Down System is undetectably screwed into the corresponding reinforced top of the Nitterhouse pedestal to securely lock down the pavers ensuring a safe, secure and level surface.

# NITTERHOUSE PEDESTAL

MATERIAL	Polypropylene and rubber (head top)
HEIGHT	1" - 39"
BASE DIAMETER & THICKNESS	8" x 1/16"
HEAD DIAMETER	7"
BASE CONTACT SURFACE AREA	49 in <sup>2</sup>
TAB HEIGHT & THICKNESS	1/2" x 5/32"
COMPRESSION STRENGTH	> 3,000 PSF
FIRE RATING	Class E (UNI EN 13501-1: 2009)
CHARACTERISTICS	Adjustable height Security lock to prevent unlocking Recyclable material



**Pedestal works with all Nitterhouse  
Architectural & Camina Paving Stones**

